


KPM-25m

光ミニパワーメータ



特性

- 2.5mmユニバーサルコネクタ
- 波長範囲 850nm~1625nm
- 数値の手動校正が可能
- シリコン製ミニケースデザインで、小型軽量
- 精度 ± 0.2 dB
- 測定範囲 $-70\sim+10$ dBm/ $-50\sim+26$ dBm
- 様々な屋外環境に対応可能な防水キーパッド
- LEDライト搭載で暗い環境にも使用可能



バックライトディスプレイ



ワンタッチスタート



オートシャットオフ



分解能0.01dB



7波長に対応



シリコン製ケース

特徴



落下防止



小型軽量



LEDライト



分離型保護カバー

KPM-25m



SC



FC



ST



LC(オプション)

波長 (nm)	850/980/1300/1310/1490/1550/1625nm
測定範囲 (dBm)	-70~+10dBm / -50~+26dBm
光コネクタ	2.5mmユニバーサルコネクタ
バッテリー	アルカリ乾電池 (AAA 1.5V電池 2本)
分解能 (dB)	0.01
動作温度	-10~+60(°C)
保存温度	-25~+70(°C)
寸法/重量	137x60x37mm / 180g

製品外観



HEAD OFFICE

KomShine Technologies Limited

CONTACT US

Add: 2F Bldg. D Qinheng Tech. Pk. Nanjing, JS, 210001, China

TEL: +86 (025) 66047688

Web: www.KomShine.com

Mail: info@komshine.com

* Komshine reserves the right to improve, enhance, or modify the features and specifications of KomShine products without prior notification.

* Company and product names appearing in this catalogue are registered marks or trademarks of respective companies.

* This catalogue is printed using environmentally friendly paper and ink.